



SUPERLIFT
SANITARY LIFTS

SCISSOR LIFTS

Tracked Scissor Lift with Outriggers

500 lbs Max. Platform Capacity | 26' Max. Height

Features

- Narrow and compact unit.
- For both indoor and outdoor work
- Auto levelling
- All-terrain capabilities
- Fully electric
- Non-marking tracks
- 4 hydraulic outriggers with auto levelling
- Foldable guardrail
- Roll-out deck extension
- Proportional controls
- Emergency stop
- Overload protection



- Descent protection alarm
- Tilt protection
- Manual lowering valve
- Flashing amber light
- Motion alarm
- Fault diagnosis system
- Hour meter
- Automatic braking system



Tracked Scissor Lift with Outriggers

500 lbs Max. Platform Capacity | 26' Max. Height

Dimensions

Max.working height	315"
Max.platform height	236.2"
Overall Length (Stowed)	90.2"
Overall Width	39.4"
Overall Height (Guardrails unfolded)	85.4"
Overall Height (Guardrails folded)	70.9"
Platform Length (Stowed)	70.9"
Platform Width	29.5"
Max Horizontal Reach (Extension)	35.4"
Ground Clearance (Stowed) From Chassis Bottom	7.3"
Ground Clearance (Stowed) From Outrigger Pad	

Weight

Overall Weight	4,080 lbs
----------------	-----------

Power

Battery	24V DC(4*12V115Ah)
Charger	85-265V36A mp

Performance

Max. Occupancy (Indoor/Outdoor) Without outriggers deployed	2/2
Max. Occupancy (Indoor/Outdoor) With outriggers deployed	2/2
Lift Capacity Without triggers deployed	500 lbs Lbs deployed
Lift Capacity With triggers deployed	500 lbs Lbs deployed
Lift Capacity (Extension deck)	264 lbs
Driving Height	No driving when lifting
Driving speed (Stowed)	0-2.0km/h
Driving speed (Raised)	No driving when lifting
Gradeability	30%
Turning Radius (Inside)	0
Turning Radius (Outside)	0
Max.Working Inclination Angle Without outriggers deployed	1.5°/2°
Max. Working Inclination Angle With outriggers deployed	0.5°/0.5°
Longitudinal Leveling Front to Back Level up	10.34°
Longitudinal Leveling Side to Side Level up	19.09°
Rise/Lower Speed (Loaded)	32/22S ±2
Controls	Proportional control