



SUPERLIFT
SANITARY LIFTS

STAINLESS STEEL SCISSOR LIFTS

Uplift Stainless Steel Self-Propelled Manlifts

500 lbs Capacity | 16' to 21' Working Heights

Features

- **All-Stainless Construction:** Fabricated from high-grade 304/316 stainless steel for maximum corrosion resistance, even in environments exposed to harsh chemicals and frequent washdowns.
- **Hygienic Design:** Fully welded framework with smooth, crevice-free surfaces that eliminate bacteria harborage points and allow effortless cleaning.
- **Self-Propelled Mobility:** Electric drive system for precise, effortless positioning without manual pushing—ideal for tight production spaces.
- **Compact Footprint:** Ultra-narrow 2.49 ft overall width for easy maneuvering in cleanrooms, corridors, and between production lines.
- **Operator Safety:** Equipped with guard rails, non-slip platform flooring, emergency stop systems, tilt sensors, and automatic brakes.
- **Low Maintenance:** Sealed electrical components and stainless cylinders reduce downtime and extend service intervals.
- **Zero Emissions:** Battery-powered operation ensures quiet, fume-free use in sterile areas.



Sales Features

- Purpose-built for hygienic environments and cleanrooms
- Meets stringent safety and cleanliness standards
- Improves productivity and reduces manual handling
- Long service life and reduced downtime with stainless construction
- Compact size fits through standard doorways and narrow aisles



Uplift Stainless Steel Self-Propelled Manlifts

500 lbs Capacity | 16' to 21' Working Heights

Specification

| MODEL | Model 1 (5.0 m) | Model 2 (5.90 m) | Model 3 (6.4 m) |
|---------------------------------|----------------------|--------------------|--------------------|
| Working Height (CE/ANSI) | 16.40 ft | 19.36 ft | 21.00 ft |
| Platform Floor Height (CE/ANSI) | 9.84 ft | 12.80 ft | 14.44 ft |
| Overall Length (with ladder) | 4.33 ft (51.97 in) | 4.33 ft | 4.59 ft (55.12 in) |
| Overall Length (without ladder) | 4.23 ft (50.79 in) | 4.23 ft | 4.46 ft (53.54 in) |
| Overall Width | 0 2.49 ft (29.92 in) | 2.49 ft | 2.49 ft |
| Overall Height (rails up) | 6.00 ft (72.05 in) | 6.36 ft (76.38 in) | 6.63 ft (79.53 in) |
| Overall Height (rails down) | 5.25 ft (62.99 in) | 5.22 ft (62.60 in) | 5.22 ft (62.60 in) |
| Platform Size (L x W) | 45.28 x 23.62 in | 45.28 x 27.56 in | 50.00 x 27.56 in |
| Ground Clearance (stowed) | 2.36 in | 2.36 in | 2.36 in |
| Ground Clearance (raised) | 0.59 in | 0.59 in | 0.59 in |
| Wheel Base | 03.25 ft (38.98 in) | 3.25 ft | 3.25 ft |
| S.W.L | 529 lb | 529 lb | 529 lb |
| Driving Wheels (Ø x width) | Ø9.06 x 3.15 in | Ø9.06 x 3.15 in | Ø9.06 x 3.15 in |
| Weight (CE/ANSI) | 1,389 lb | 1,488 lb | 1,526 lb |



Applications: Pharmaceutical cleanrooms, food & beverage production lines, medical device assembly areas, semiconductor & electronics cleanrooms, laboratories & research facilities.